



SPRAY POLYURETHANE FOAM SYSTEM



InsulBloc is a spray-in-place closed cell polyurethane foam insulation marketed for use in commercial and residential construction. All insulation systems provide R-Value, the resistance to heat flow by thermal diffusion. In addition to a high R-value per inch InsulBloc provides the air barrier, water resistive barrier, and moisture vapor retarder. InsulBloc provides greater performance and value for your insulation dollar than alternate multiple product systems.

InsulBloc is an Air Barrier Material per ABAA certification and approved for application in ABAA designated projects.

InsulBloc is approved for use in multiple UL Fire Resistive Designs. See U901, U902, U904, U905, U906, U907, U424, U460, U391, U495. Check with NCFI for additional listings.

R* Values	
Thickness (inches)	R Value (°F·hr·ft ² / Btu)
1	6.8
2	13
3	19
4.75	30
12	76

*Note: As with all insulating materials, the R value will vary with age and use conditions.

Property		Test Method	Result
Air Leakage		ASTM E 283 & ASTM E 2178	0.000 cfm/ft ²
			0.000 cfm/ft ²
Water Resistance	AC 71	AATCC127-1998	No failure
		ASTM E 331	No Penetration
Vapor Permeance		ASTM E 96	1.3 perm-inch

Read This Before you Buy

What you should know about R values

The chart shows the R value of this insulation. R means resistance to heat flow. The higher the R value, the greater the insulating power. Compare insulation R values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel. To get the marked R-value, it is essential that this insulation be installed properly.